

Final Report on ONR Grant No. N00014-02-1-0984

Nanostructures for Enhanced Electron/Hole Conversion

Principal Investigators:

Arthur C. Gossard and Herbert Kroemer

Materials Department, University of California
Santa Barbara, CA 93106-5050
gossard@engineering.ucsb.edu; kroemer@ece.ucsb.edu

Submitted to:



Office of Naval Research

Attention: Dr. Colin H. Wood 875 N. Randolph Street, Suite 1425 Arlington, VA 22203-1995

March 13, 2009

20090319159

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including

1. REPORT DATE (DD-MM-YYYY) 2. REPORT TYPE			_		3. DATES COVERED (From - To)		
3/13/20	09		Final Technical	Report		10/1/02 - 9/30/06	
4. TITLE AND SUBT	TLE	. 1			5a. CO	NTRACT NUMBER	
	1 1 1 1 1 1	71.1.0	•				
Nanostructures for Enhanced Electron/Hole Conversion					5b. GRANT NUMBER		
						N00014-02-1-0984	
					5c. PR	OGRAM ELEMENT NUMBER	
6. AUTH OR(S)					5d. PROJECT NUMBER		
Arthur C. Gossard and Herbert Kroemer					5e. TASK NUMBER		
					30. 17	OK NOMBER	
					5f. WO	RK UNIT NUMBER	
					312		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)					1	8. PERFORMING ORGANIZATION	
The Regents of the University of California						REPORT NUMBER	
Office of Research							
3227 Cheadle Hall, 3	rd Floor						
Santa Barbara, CA 93106-2050							
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)						10. SPONSOR/MONITOR'S ACRONYM(S)	
Office of Naval Research						ONR	
140 Sylvester Road						ONK	
Building 140, Room 218						11. SPONSOR/MONITOR'S REPORT	
San Diego, CA 92106-3521						NUMBER(S)	
12. DISTRIBUTION/A	VAILABILI1	YSTATEMENT					
"Approved for Relea	aar Dioteibur	ion is Unlimita	4 "				
Approved for Relea	se, Distribui	ion is Chilling	J.				
13. SUPPLEMENTAR	RY NOTES						
14. ABSTRACT							
						structures containing embedded metallic	
•				-		ated epitaxial metallic nanoparticles of erbium	
						xy. The metallic nanoparticles in semiconductors	
						3) electron/hole tunnel junction enhancement, 4)	
						sma resonances. Tunnel currents of GaAs np	
						stron-hole recombination times in a series of	
						epitaxial growth of GdN on GaN. This research	
						power generation materials, for new materials fo	
		etection and for	development of highly of	conducting con	tacts for	the nitride semiconductors.	
15. SUBJECT TERM	5						
				140 411/22	T		
16. SECURITY CLAS			17. LIMITATION OF ABSTRACT	18. NUMBER		AME OF RESPONSIBLE PERSON	
a. REPORT b. A	BOTRACT	c. THIS PAGE	7,5511,7791	PAGES		r C. Gossard	
				7	19D. IE	ELEPHONE NUMBER (Include area code)	

Final Technical Report:

Nanostructures for Enhanced Electron/Hole Conversion

A. C. Gossard and H. Kroemer, University of California Santa Barbara

Office of Naval Research Grant No. N00014-02-1-0984

Final Report for 07/31/2003 to 07/31/2006:

In this program we created, studied, and developed applications for epitaxial metal-semiconductor heterostructures and nanostructures. The epitaxial metal-semiconductor nanocomposites are new electronic materials that can have substantially different properties from conventional doped semiconductors. Our approach was to use molecular beam epitaxy (MBE) growth to create epitaxial metal-semiconductor structures containing embedded nanoparticles, epitaxial films and metal-semiconductor junctions. Unlike current electronic technologies that must rely on individual dopant atoms to provide carriers and on highly imperfect polycrystalline metal films to provide electrical contacts, the new epitaxial nanoparticles and films provide a wide distribution of electron energies within a semiconductor and provide a very controlled and perfect contact to semiconductors. We studied these materials with the goal of reduction and engineering of semiconductor p-n junction barriers by embedding metallic nanoparticles in the junctions. We incorporated epitaxial metallic nanoparticles of erbium arsenide and erbium antimonide in GaAs, InGaAs and GaSb structures by molecular beam epitaxy growth. Collaborating faculty member Susanne Stemmer obtained direct evidence from Z-contrast scanning transmission electron microscopy that the metal nanoparticles of ErAs grow in a perfectly registered rocksalt structure within the zincblende semiconductor host. Current-voltage measurements showed that

1) Tunnel currents of GaAs np junctions were enhanced by up to five orders of magnitude at room temperature at one volt forward bias by incorporation of 1.2 monolayers of ErAs deposition at the junction between the n $(5x10^{18} \text{ cm}^{-3})$ and p $(2x10^{19} \text{ cm}^{-3})$ GaAs. The tunnel currents exceeded 10^5 Amps/cm² at +1 V forward bias.

- 2) The tunnel current enhancement was approximately one order of magnitude greater at +1 V bias for ErAs-enhanced GaAs junctions for p grown on n compared to n grown on p.
- 3) The tunnel current enhancement was approximately one order of magnitude greater at +1 V bias for ErAs-enhanced GaAs junctions relative to Al₁Ga₉As junctions.
- 4) The tunnel current enhancement was approximately one order of magnitude greater at +1 V bias for $p = 2x10^{19}$ cm⁻³ doping of GaAs junctions compared to $p = 4x10^{18}$ cm⁻³ doping.
- 5) The tunnel current enhancement was approximately one order of magnitude greater at +1 V bias for 1.2 monolayers of ErAs deposition compared to 0.2 monolayers of ErAs deposition.
- 6) The form of the tunneling current versus voltage characteristic in the enhanced junctions was well represented by a model of tunneling in series through back to back metal- semiconductor junctions.

The first metal-semiconductor junctions (of TiPtAu on n-doped GaAs (n = 1×10^{17} cm⁻³)) with and without a 0.6 monolayer deposition of ErAs two nanometers below the metal-semiconductor interface were also grown and studied. The structure with ErAs had a reduced Schottky barrier and a more ideal tunnel characteristic compared to structures with no enhancing ErAs deposition.

Carrier concentrations and electron-hole recombination rates were measured in a series of ErAs/InGaAs superlattices. Samples with 40 nm periods showed a decrease in conduction electron concentration as the deposition of ErAs increased from 0.4 to 1.6 monolayers. Samples with depositions of 1.2 and 1.6 monolayers froze out at low temperature, while samples with depositions of 0.4 and 0.8 monolayers remained fully metallic with $\sim 10^{12}$ electrons per cm² per layer of ErAs. Partial compensation of the carriers was achieved by modulation doping the regions near the ErAs layers with beryllium acceptors. Reduction of the superlattice period from 40 nm to 5 nm reduced electron-hole recombination times to ~ 2 ps (at 40 nm period) and ~ 0.05 ps (at 5 nm period).

In cooperation with Professor Elliott Brown, Gossard's students grew and characterized epitaxial Schottky diodes of epitaxial ErAs films on InGaAlAs of various Al contents. Reducing the Al content in the InGaAlAs reduced the Schottky barrier height continuously down to and including zero eV.

Diodes with optimum responsivity at zero applied bias were produced and measured.

We also grew fully epitaxial diodes of n-doped InAs on p-doped GaSb. Forward currents of >1000 Amps per cm² were measured at +1 Volt bias and were limited primarily by Ohmic contact resistance.

The metallic nanoparticles in semiconductors produced: 1) electrical doping of semiconductors, 2) electron/hole recombination enhancement, 3) electron/hole tunnel junction enhancement, 4) thermal conductivity control, 5) microwave rectification improvement and 6) strong electron plasma resonances.

ErAs particles in GaAs p-n tunnel junctions allowed much stronger tunneling than conventional p-n junctions. p-ErAs-n junctions showed up to 10⁵ times more current than comparable p-n junction at 1 Volt forward bias. We synthesized cascaded photovoltaics with ErAs enhanced tunnel junctions that produced CW radiation up to 2 Thz.

We also formed epitaxial thin films of ErAs on GaAs and InGaAlAs for highly ideal and engineerable low-defect contacts and barriers for sensitive low noise mm-wave and THz detection. We measured NEP of <9x10⁻¹³ W Hz^{-1/2} giving -63 dBm sensitivity at 3.1 GHz with a 8kHz bandwidth.

We developed epitaxial metal-semiconductor heterostructures and nanostructures with record-breaking performance in several areas.

- 1. Cascaded solar cells with increased efficiency. Grew cascaded AlGaAs solar cells with ErAs-enhanced tunnel junctions with output voltages of 2.1 Volts (versus 1.2 Volts with conventional tunnel junctions).
- 2. **ErAs nanoparticle arrays**. Produced high densities of metal nanoparticles in InGaAs by co-deposition of ErAs and semiconductor species. The arrays have high electrical conductivity, low thermal conductivity and are promising for thermoelectric power generation
- 3. **Highly conductive epitaxial Ohmic contacts**. Produced epitaxial ErAs epitaxial films on graded InGaAs structures. Contact resistances are less than 2 Ohm-micron².
- 4. Low noise epitaxial Schottky microwave detectors. Produced epitaxial ErAs/lnAlGaAs detectors with noise equivalent power below 10⁻¹¹ W/Hz^{1/2} at 640 GHz.

- 5. **Terahertz detectors**. Produced ErAs nanoparticles in GaAs with best reported bandwidth and efficiency for Terahertz detectors (10 times better than radiation-damaged SOS detectors and LT-GaAs detectors).
- 6. **GdN on gallium nitride:** We produced the first epitaxial growth of GdN on GaN. We found growth conditions to produce micron-thick epitaxial films of GdN on GaN templates. We produced GdN (111) films with rocksalt structure on (0001) GaN at substrate temperatures below T = 500C.

The research accomplished under this grant thus established a foundation for development of highly conducting contacts for the nitride semiconductors, for development of improved artificially structured thermoelectric power generation materials, and for new materials for Terahertz wave generation and detection.

Publications:

Driscoll DC, Hanson MP, Mueller E, Gossard AC. Growth and microstructure of semimetallic ErAs particles embedded in an InGaAs matrix. Journal of Crystal Growth, vol.251, no.1-4, April 2003, pp.243-7

Sukhotin M, Brown ER, Driscoll D, Hanson M, Gossard AC. Picosecond photocarrier-lifetime in ErAs:InGaAs at 1.55 microns. Applied Physics Letters, vol.83, no.19, 10 Nov. 2003, pp.3921-3

Pohl P, Renner FH, Eckardt M, Schwanhausser A, Friedrich A, Yuksekdag O, Malzer S, Dohler GH, Kiesel P, Driscoll D, Hanson M, Gossard AC. Enhanced recombination tunneling in GaAs pn junctions containing low-temperature-grown-GaAs and ErAs layers. Applied Physics Letters, vol.83, no.19, 10 Nov. 2003, pp.4035-7.

Hanson MP, Driscoll DC, Kadow C, Gossard AC. Metal/semiconductor superlattices containing semimetallic ErSb nanoparticles in GaSb.

[Journal Paper] Applied Physics Letters, vol.84, no.2, 12 Jan. 2004, pp.221-3

Hanson MP, Driscoll DC, Zimmerman J, Brown ER, Gossard AC. Subpicosecond photocarrier lifetimes in GaSb/ErSb nanoparticle superlattices at 1.55 micron. Applied Physics Letters, vol. 85, no. 15 (Oct. 11, 2004), pp. 3110-3112

Bjarnason JE, Chan TLJ, Lee AWM, Brown ER, Driscoll DC, Hanson M, Gossard AC, Muller RE. ErAs:GaAs photomixer with two-decade tunability and 12 microwatt peak output power. Applied Physics Letters, vol.85, no.18, 1 Nov. 2004, pp.3983-5.

Hanson MP, Driscoll DC, Zimmerman JD, Gossard AC, Brown ER. Subpicosecond photocarrier lifetimes in GaSb/ErSb nanoparticle superlattices at 1.55 microns. Applied Physics Letters, vol.85, no.15, 11 Oct. 2004, pp.3110-12.

Dorn A, Peter M, Kicin S, Ihn T, Ensslin K, Driscoll D, **Gossard** AC. **Charging effects of ErAs islands embedded in AlGaAs heterostructures.** *Elsevier. Physica E - Low-Dimensional Systems & Nanostructures, vol.21, no.2-4, March 2004, pp.426-9.*

Driscoll DC, Hanson MP, Gossard AC. Carrier compensation in semiconductors with buried metallic nanoparticles. Applied Physics Letters, vol. 97, no. 1, January 1, 2005, p. 016012

Driscoll DC, Hanson MP, **Gossard** AC, Brown ER. **Ultrafast photoresponse at 1.55 mm in InGaAs with embedded semimetallic ErAs nanoparticles**. *Applied Physics Letters*, vol. 86, no. 5 (January 31,2005) p. 051908

G H Döhler, F Renner, O Klar, M Eckardt, A Schwanhäußer, S Malzer, D Driscoll, M Hanson, A. C. Gossard, G Loata, T Löffler and H Roskos. **THz-photomixer based on quasi-ballistic transport.** *Semiconductor Science and Technology, vol. 20, July, 2005, pp. S178-S190.*

Klenov DO, Zide JM, Zimmerman JD, Gossard AC, Stemmer S. Interface atomic structure of epitaxial ErAs layers on (001) InGaAs and GaAs. Applied Physics Letters, vol.86, no.24, 13 June 2005, pp.241901-1-3

Prasankumar RP, Scopatz A, Hilton DJ, Taylor AJ, Averitt RD, Zide JM, Gossard AC. Carrier dynamics in self-assembled ErAs nanoislands embedded in GaAs measured by optical-pump terahertz-probe spectroscopy. Applied Physics Letters, vol.86, no.20, 16 May 2005, pp.201107-1-3.

Russell KJ, Appelbaum I, Narayanamurti V, Hanson MP, **Gossard** AC. **Transverse momentum nonconservation at the ErAs/GaAs interface.** [Journal Paper] *Physical Review B-Condensed Matter, vol.71, no.12, 15 March 2005, pp.121311-1-4*

Klenov DO, Driscoll DC, Gossard AC, Stemmer S. Scanning transmission electron microscopy of ErAs nanoparticles embedded in epitaxial In/sub 0.53/Ga/sub 0.47/As layers. Applied Physics Letters, vol.86, no.11, 14 March 2005, pp.111912-1-3.

Driscoll DC, Hanson MP, Gossard AC, Brown ER. Ultrafast photoresponse at 1.55 microns in InGaAs with embedded semimetallic ErAs nanoparticles. Applied Physics Letters, vol.86, no.5, 31 Jan. 2005, pp.51908-1-3.

Driscoll DC, Hanson MP, Gossard AC. Carrier compensation in semiconductors with buried metallic nanoparticles. *Journal of Applied Physics*, vol. 97, no. 1, 1 Jan. 2005, pp. 16102-1-3.

Trumm S, Betz M, Sotier F, Leitenstorfer A, Schwanhausser A, Eckardt M, Schmidt O, Malzer S, Dohler GH, Hanson M, Driscoll D, Gossard AC. Ultrafast spectroscopy of impact ionization and avalanche multiplication in GaAs. Applied Physics Letters, vol. 88, no. 13 (March 27, 2006) p. 132113.

Hanson, MP, Gossard, AC, Brown, ER. ErAs as a transparent contact at 1.55 microns. Applied Physics Letters, vol. 89, no. 11 (Sept. 11, 2006), p. 111908